

## REVOGEAR™ – HIGH - PERFORMANCE SYNTHETIC EXTREME PRESSURE GEAR OIL

REVOGEAR™ is a premium, high-performance fully synthetic lubricant for use in Gearboxes requiring an Extreme-Pressure Gear Oil.

REVOGEAR™ has been specifically developed to work in heavily loaded and demanding applications and incorporates advanced additive and base oil technology that greatly improves equipment reliability and service life. Our unique additive technology is proven to make equipment run better for longer and more efficiently. REVOGEAR greatly reduces energy consumption and will increase the mean time between planned/unplanned maintenance and meets the following specifications:

GL4/GL 5 LS , SAEJ2360 , MT1 , US STEEL 224 , 51517 PART III , MACK GO-J , MACK GO-J PLUS , SCANIA STO 1:0.

### PERFORMANCE ADVANTAGES

- High Film Strength
- Shock Load Protection
- Saves Energy
- Extremely Clean
- Reduces Bearing Vibrations
- Longer Oil Life
- Excellent Corrosion Protection
- Synthetic Solvency
- Compatible with Other Oils
- Fluorescent Under UV Light

	REVOGEAR GRADES						
	46	68	100	150	220	320	460
Viscosity							
cST @ 40°C	46	68	100	150	220	320	460
cST @ 100°C	7.6	9.9	12.9	17.2	22.4	29.7	38.6
Viscosity Index	132	128	125	125	124	127	126
Flash Point ° C	246	260	266	270	275	275	275
Pour Point ° C	-47	-38	-38	-30	-30	-30	-30
D-130 Copper Corrosion							
3 hrs. @ 210°F	1B	1B	1B	1B	1B	1B	1B
250 hrs. @ 210°F	1B	1B	1B	1B	1B	1B	1B
D-665 Rust Test							
Fresh Water	PASS	PASS	PASS	PASS	PASS	PASS	PASS
Salt Water	PASS	PASS	PASS	PASS	PASS	PASS	PASS
FZG Test	12	12	12	12	12	12	12
Specific Gravity	0.855	0.861	0.862	0.862	0.868	0.876	0.886