



# FLEET MAX ULTRA™

## CI-4/CI4+ HIGH PERFORMANCE DIESEL ENGINE OIL

**FLEET MAX ULTRA™** engine oil is recommended for use in diesel applications including automotive, commercial fleet and stationary diesel engines. Fleet Max Ultra engine oils are tough, long life, high performance oils that deliver superior protection and enhanced performance to petrol and diesel engines. It gains its performance advantages from a blend of synthetic base oils plus Revolutions' advanced **DynaSyn™** additive technology. Revolutions' proprietary additive technology greatly reduce engine wear, including ring, cylinder and bearing wear. It is extremely tenacious, adheres to engine surfaces and remains after shutdown, which provides protection upon initial startup.

<b>Performance Characteristics:</b>	
<ul style="list-style-type: none"> <li>• Improved Wear Protection</li> <li>• Increases Power</li> <li>• Saves Fuel</li> <li>• Keeps Engines Clean</li> <li>• Extended Drain Intervals</li> <li>• Excellent Corrosion Protection</li> <li>• Compatible with Seals</li> <li>• Compatible with Other Oils</li> <li>• Reduces Emissions</li> </ul>	<p><b>Fleet Max Ultra™</b> is fully synthetic oil that protects bearings far beyond the ability of other oils and is able to carry up to 700 percent greater loads, eliminating engine wear.</p> <p><b>Fleet Max Ultra™</b> Engine Oil has a low coefficient of friction and is able to produce consistent and measurable fuel savings.</p> <p><b>Fleet Max Ultra™</b> 15W40 meets API CI-4 PLUS/SM, ACEA A3/ B3/ E3/ E5/ E7, CAT ECF-3, Cummins CES 20081, MB 228.31, Mack EO-O Premium Plus 07 and Volvo VDS-4 engine oil requirements.</p> <p><b>Fleet Max Ultra™</b> Engine Oil has outstanding oxidation stability which eliminates lacquer and varnish deposits. It also stops the oil from thickening which leads to a loss of lubricity that shortens oil and engine life.</p> <p><b>Fleet Max Ultra™</b> natural solvency cleans up deposits and keeps engines clean.</p>

	<b>Fleet Max Ultra</b>	
	10W30	15W40
Viscosity		
cST @ 40°C	66.8	105.3
cST @ 100°C	10.4	14.8
Viscosity Index	143	146
Flash Point ° C	220	228
Cold Crank Viscosity		
cP @ - 25 °C	4852	
cP @ - 20 °C		5179
TBN	11	11

# GEAR MAX ULTRA™

## API GL 4 / GL 5 HIGH PERFORMANCE GEAR OIL

**GEAR MAX ULTRA™** is recommended for use in truck and automotive front or rear differentials, manual transmissions and lower gear units of marine engines that specify use of an API GL-5 or GL-4 fluid. Gear Max Ultra is a tough, high performance automotive gear oil designed to provide advanced protection to heavily loaded gears while maximizing power throughout the drive train. Gear Max Ultra outperforms ordinary gear oils by combining the highest quality synthetic oils with Revolutions proprietary **DynaSyn™** additive technology. Gear Max Ultra makes gears run more efficiently and last longer. Gear Max Ultra is formulated with a friction modifier additive so no additional additives are necessary.

<b>Performance Characteristics:</b>	
• High Film Strength	<b>Gear Max Ultra™</b> Series gear oils are fully synthetic oils that protects bearings far beyond the ability of other oils due its exceptionally high film strength
• Extended Drain Intervals	<b>Gear Max Ultra™</b> has an extremely low coefficient of friction and is proven to save energy over conventional oils
• Saves Fuel	<b>Gear Max Ultra™</b> tough oil film and its ability to micro-polish contacting surfaces provides superior bearing lubrication
• Increases Power	<b>Gear Max Ultra™</b> has outstanding oxidation stability that greatly extends oil change intervals
• Reduces Maintenance	
• Compatible with Other Oils	
• Environmentally Responsible	
• Safe for Limited Slip Differential	

	<b>GEAR MAX ULTRA</b>			
	75W90	75W140	80W90	85W140
Viscosity				
cST @ 40°C	118	68.4	81.8	86.4
cST @ 100°C	17	11.7	13.2	13.4
CP @ - 12 ° C	-	-	-	36'600
CP @ - 26 ° C	-	-	10'800	-
CP @ - 40 ° C	123'000	137'000	-	-
Flash Point ° C	195	190	200	190
Pour Point ° C	- 50	- 55	- 40	- 36
Corrosion Test	PASS	PASS	PASS	PASS
Rust Test	PASS	PASS	PASS	PASS
Foam test	PASS	PASS	PASS	PASS
Timken OK Load	PASS	PASS	PASS	PASS
Four Ball EP Test	100+	100+	100+	100+



# FLEET MAX MPG™

## HIGH PERFORMANCE MULTI-PURPOSE GREASE

**FLEET MAX MPG™** is a multi-purpose grease with a wide range of applications and is recommended for bearings and general purpose use. Fleet Max MPG is a high performance, multi-service, aluminum complex, synthetic grease. Its outstanding performance is achieved through its superior blend of synthetic base oils plus **DynaSlide™** additive technology, Revolutions' unique, proprietary, noncorrosive EP additive technology. Fleet Max MPG significantly increases bearing life and equipment reliability and makes bearings run smoother, cooler, quieter, longer and more efficiently.

### Performance Characteristics:

- Improved Wear Protection
- Reduces Vibration
- Aluminium Complex Grease
- Multi Temperature Applications
- Excellent Water Resistance
- Excellent Corrosion Protection

**Fleet Max MPG™** has exceptional film strength which provides superior protection to anti-friction and journal bearings.

**Fleet Max MPG™** tough oil film coupled with its ability to micro-mend contacting bearing elements provides superior bearing lubrication and reduced vibrations.

**Fleet Max MPG™** has an aluminium complex base which greatly improves shear stability, water resistance and high temperature performance.

**Fleet Max MPG™** encompasses both good low temperature pumpability and excellent high temperature stability and is suitable for centralized pressure systems.

**Fleet Max MPG™** will not mix with water and has great resistance to water wash off.

	<b>FLEET MAX MPG</b>
NLGI Grade	2
Thickener Type	Aluminium Complex
Thickener Content	7.50%
Consistency	Buttery
Fluid Type	Synthetic
Viscosity @ 40°C	150
Drop Point °C	270
Copper Corrosion Test	1A
Cone Penetration, Worked 60X	280
Water Washout % @79°C	<5
Four Ball EP Test, Load Wear Index	65.2
Four Ball EP Test, Weld Load Kgf	400

## COOLANT SYSTEM OPTIMIZER AND CONDITIONER

---

**ULTRACOOOL™** is a high performance cooling system optimizer and conditioner. With an advanced 2 in 1 formula, Ultracool provides excellent corrosion inhibition as well outstanding wetting ability for year round protection against corrosion and heat.

Extensive testing has shown that Ultracool reduces coolant temperatures beyond that of conventional coolants.

**Performance Characteristics:**

- Reduces Surface Tension
- Reduces Hot Spots
- Prevents Overheating
- Compatible with OEM Coolants
- Pre Mixed Ready to Use
- Excellent Corrosion Protection

**Ultracool™** reduces the surface tension of a coolant allowing more heat to be transferred resulting in more power.

**Ultracool™** reduces hotspots in the engine and cylinder head reducing the possibility of engine failure.

**Ultracool™** help prevent overheating and keeps the cooling system clean extending the life of the water pump.

**Ultracool™** is a premixed ready to use product that is poured straight into the cooling system, no need to mix or dilute

# If your fleet could choose its own oil, it would choose Revolution Oil's Fleet Max

Upgrading to Revolution Oil vastly improves equipment reliability, which saves you money. Revolution Oil offers only the most technologically advanced, high performance lubricants available on the market today. Its oils are tested and proven to decrease maintenance and fuel costs. Fuel savings alone typically exceed the total cost of the oil within a few months, virtually eliminating all lubricant expenses. So change your oil to Revolution Oil today and discover that increased reliability and reduced maintenance costs are just an oil change away.

**Revolution Oil / 12B Engwena Road / Sebenza / 011 024 6434 / [www.revolutionoil.co.za](http://www.revolutionoil.co.za)**

---

**ULTRA PERFORMANCE SYNTHETIC OIL**