

## **REVOCOMP<sup>™</sup> – HIGH - PERFORMANCE SYNTHETIC COMPRESSOR OIL**

**REVOCOMP<sup>™</sup>** is a premium, high-performance synthetic lubricant developed for use in various compressor application types such as rotary screw, lobe, and vane compressors.

**REVOCOMP<sup>™</sup>** has been specifically developed to work in high-temperature and demanding compressor applications and incorporates superior additive and base oil technology that greatly improves compressor reliability and service life. Our unique additive technology is proven to make equipment run better for longer and more efficiently.

**REVOCOMP<sup>™</sup>** greatly reduces energy consumption in all compressor applications and will increase the mean time between planned/unplanned maintenance and is an ideal replacement for conventional oils that operate at high temperature and that rely on their viscosity for protection.

## **PERFORMANCE ADVANTAGES**

- High Film Strength
- <u>Rapidly Separates from Water</u>
- <u>Reduces Energy Consumption</u>
- <u>Extremely Clean</u>
- <u>Reduces Vibrations</u>
- Longer Oil Life
- <u>Excellent Corrosion Protection</u>
- Synthetic Solvency
- <u>Compatible with Other Oils</u>
- Fluorescent Under UV Light

	REVOCOMP GRADES				
	32	46	68	100	150
Viscosity					
cST @ 40°C	32	46	68	100	150
cST @ 100°C	5.8	7.8	10.2	13.7	18.6
Viscosity Index	134	136	135	138	140
Flash Point ° C	246	260	266	270	275
Pour Point ° C	-47	-38	-38	-30	-30
D-130 Copper Corrosion					
3 hrs. @ 210°F	1A	1A	1A	1A	1A
250 hrs. @ 210°F	1A	1A	1A	1A	1A
D-665 Rust Test					
Fresh Water	PASS	PASS	PASS	PASS	PASS
Salt Water	PASS	PASS	PASS	PASS	PASS
Specific Gravity	0.85	0.855	0.858	0.857	0.864

## UNPARALLELED LUBRICATION PERFORMANCE<sup>TM</sup>